

AIR-POWERED AIRLESS SPRAY PUMP

無氣霧噴漆泵浦



技術 • 效率 • 品質 • 服務

春泰機械工程有限公司成立於民國62年，從事各種塗裝設備之生產研究開發業務：

經不斷的努力與研究，至今已能生產精密的自動化靜電噴漆機器及塗裝設備，傳統的空气式(AIRSPRAY)混氣式(AIR MIX)和無氣式(AIRLESS)輸送泵浦，其他相關設備如水洗式NO PUMP噴漆房，手持靜電塗裝機等等，在功能及品質方面皆媲美進口貨，本公司除製造及售後服務外，亦作整套最新塗裝設施之規劃，設計及施工等業務，歡迎各界洽詢。

AIR-POWERED AIRLESS SPRAY PUMP

無氣霧噴漆泵浦



CTP-7M-30:1(107-032)

ACCESSORIES(附件):



噴漆槍
A500(350-001)
AIRLESS GUN



自動噴槍(207-614)
AUTOMATIC GUN



3/8" 高壓穩壓器(274-020)
FLUID HIGH PRESSURE REGULATOR



AIRLESS POLE GUN

3/8" 高壓蓄壓過濾器(290-020)
3/4" 高壓蓄壓過濾器(290-060)
HIGH PRESSURE FILTER

適用:

一般塗料、PVC、PU、水性、中高粘度塗料的中大量噴塗，及塗料中央循環供漆系統，氣動式安全性高、損耗少使用壽命長。

特點:

- 污染少
氣動高壓泵浦，塗料直接霧化，噴塗時無反彈，作業環境改善。
- 噴塗速度快
無氣式噴槍，噴塗速度較一般噴槍快3-10倍。
- 節省塗料、人工
附著率達80%，大量節省塗料操作時間縮短節省人工。

APPLICATION:

General PVC, PU, water-based, medium and high viscosity coatings; suitable for medium and high volume spraying; high safety, low waste, long life.

FEATURES:

- **LOW POLLUTION:**
Air powered high pressure pump; the coating is directly aerated; no reacting when spraying the paint; the operating environment is improved.
- **HIGH SPRAYING SPEED**
Airless spraying gun; the speed is 3-10 times than that by ordinary spraying gun.
- **SAVES PAINT AND LABOR:**
The adhesion rate is 80%; save much paint and shorten the working hours and labor.

CTP-6M-30 : 1 (106-032)

Fluid pressure ratio: 30 : 1 (壓力比)
Delivery: 0~4 l/min (吐出量)
Maximum outlet pressure: 200 kg/cm²
Air motor effective diameter: 153 mmφ

Air motor stroke: 100 mm
Air motor speed: 0~60 cycles/min
Air inlet: 3/8" PT
Fluid outlet: 3/8" PT

CTP-7M-30 : 1 (107-032)

Fluid pressure ratio: 30 : 1 (壓力比)
Delivery: 0~9 l/min (吐出量)
Maximum outlet pressure: 200 kg/cm²
Air motor effective diameter: 178 mmφ

Air motor stroke: 120 mm
Air motor speed: 0~60 cycles/min
Air inlet: 1/2" PT
Fluid outlet: 3/4" PT

CTP-10M-45 : 1 (108-045)

Fluid pressure ratio: 45 : 1 (壓力比)
Delivery: 0~12 l/min (吐出量)
Maximum outlet pressure: 270 kg/cm²
Air motor effective diameter: 254 mmφ

Air motor stroke: 120 mm
Air motor speed: 0~50 cycles/min
Air inlet: 3/4" PT
Fluid outlet: 1" PT



春泰機械工程有限公司
Fuspec Taiwan Pty., Ltd.

桃園縣龜山鄉志義路2段260巷65號
No. 65, Lane. 260, Sec. 2, Zhong Yi Rd.,
Guei Shan Town, Taoyuan 333, Taiwan
TEL: +886 3 3185977 FAX: +886 3 3185978
E-mail: fpec@ms22.hinet.net